G5 Tyre Inflation equipment

PN-132-N2P

Automatic Nitrogen Generator and filling system

Features

- Generate Nitrogen from normal compressed air
- Internal tank for Nitrogen storage (50L)
- 2 Pre filters to improve nitrogen quality
- Automatic inflation system with auto start
- Automatic zero drift compensation
- Audio and Visual end of cycle indicators
- Built in Nitrogen purge and fill cycle
- Remove air and replace with nitrogen cycle
- Adjustable over pressure setting
- Self diagnostic features



Power Supply	100 - 240 Vac
Weight	97kg
Air Input Pressure	6 - 8.5Bar
Air Input Flow	250L/min/8.0cfm
Nitrogen Output	42L/min @ 8Bar
Nitrogen Purity	95 - 99%
Resolution	0.1Bar
Units	PSI/Bar/kPa
Maximum Tank Pres.	7 Bar

Typical Operation

1. Set target pressure
2. Connect hose to tyre valve

3a. For TOP-OFF : Press Fill/Purge button once

3b. For Air to Nitrogen Conversion : Press and hold Fill/Purge button for 2 sec

4. When unit beeps and display flashes target pressure inflation is complete

E-MAIL info@hge.co.za
WEBSITE www.hge.co.za
TEL 012 330 0540
FAX 012 330 0860

HIGHVELD Garage Equipment CC
CK 85/005300/23