MAS-6400

Spray Booth

Technical Data

Booth Outside (mm)	7050x5250x3600
Booth Inside (mm)	6900x3900x2800
Working Door (mm)	300x2700
Personnel Door (mm)	800x2000
Total Power	16KW 380v/3 Phase/ 50Hz



Features

- Wall & Ceiling: Panels 75 mm thick, with foam in the middle and colour steel on both sides
- Basement system: Galvanized metal pedestal with filter tray
  Galvanized grid plates
  Galvanized Diamond Plates
- Heating system: Diesel Burner (Italy) 200000kcal/h
  Stainless Steel Heating Exchanger
  5-10 minutes to reach a temperature of 60-80°C
  Cabinet
  Air Ducts
- Filter System: Primary filter (filtering rate > 83%)
  Air-intake filter (filtering rate > 97%)
  Air-exhaust filter (filtering rate > 70%)
- Air System: Air-Intake Fans: Centrifugal Fans with 4 KW motor each (air volume 24000m3/h)
  Air-Exhaust Fans: Centrifugal Fans with 5.5KW motor (air volume 20000m3/h)
  Cabinet for the fans
  Air Ducts
  Air Damper (electric)
- Illumination: Ceiling and side lights with light fixtures (36w each)
- All hardware, fasteners and sealants are included

E-MAIL info@hge.co.za
WEBSITE www.hge.co.za

TEL 012 330 0540
FAX 012 330 0860

HIGHVELD
Garage Equipment CC
CK 85/005300/23